

## General Description

The GreenMOS<sup>®</sup> high voltage MOSFET utilizes charge balance technology to achieve outstanding low on-resistance and lower gate charge. It is engineered to minimize conduction loss, provide superior switching performance and robust avalanche capability.

The GreenMOS<sup>®</sup> Z series is integrated with fast recovery diode (FRD) to minimize reverse recovery time. It is suitable for resonant switching topologies to reach higher efficiency, higher reliability and smaller form factor.

## Features

- Low  $R_{DS(ON)}$  & FOM
- Extremely low switching loss
- Excellent stability and uniformity

GreenMOS<sup>®</sup>



## Applications

- PC power
- LED lighting
- Telecom power
- Server power
- EV Charger
- Solar/UPS


## Key Performance Parameters

| Parameter                         | Value | Unit       |
|-----------------------------------|-------|------------|
| $V_{DS}$                          | 600   | V          |
| $I_D$ , pulse                     | 85    | A          |
| $R_{DS(ON)}$ , max @ $V_{GS}=10V$ | 92    | m $\Omega$ |
| $Q_g$                             | 58    | nC         |
| PD                                | 220   | W          |

## Marking Information

| Product Name     | Package | Marking       |
|------------------|---------|---------------|
| OSG60R092KT3ZF-F | TO263   | OSG60R092KT3Z |

## Package & Pin Information



**Absolute Maximum Ratings** at  $T_j=25^{\circ}\text{C}$  unless otherwise noted

| Parameter                                                                 | Symbol                | Value      | Unit               |
|---------------------------------------------------------------------------|-----------------------|------------|--------------------|
| Drain-source voltage                                                      | $V_{DS}$              | 600        | V                  |
| Gate source voltage (static)                                              | $V_{GS}$              | $\pm 20$   | V                  |
| Gate source voltage (dynamic)                                             |                       | $\pm 30$   | V                  |
| Continuous drain current <sup>1)</sup> , $T_C=25^{\circ}\text{C}$         | $I_D$                 | 40         | A                  |
| Continuous drain current <sup>1)</sup> , $T_C=100^{\circ}\text{C}$        |                       | 25.3       |                    |
| Pulsed drain current <sup>2)</sup> , $T_C=25^{\circ}\text{C}$             | $I_{D, \text{pulse}}$ | 85         | A                  |
| Continuous diode forward current <sup>1)</sup> , $T_C=25^{\circ}\text{C}$ | $I_S$                 | 40         | A                  |
| Diode pulsed current <sup>2)</sup> , $T_C=25^{\circ}\text{C}$             | $I_{S, \text{pulse}}$ | 85         | A                  |
| Power dissipation <sup>3)</sup> , $T_C=25^{\circ}\text{C}$                | $P_D$                 | 220        | W                  |
| Single pulsed avalanche energy <sup>5)</sup>                              | $E_{AS}$              | 658        | mJ                 |
| MOSFET dv/dt ruggedness, $V_{DS}=0\ldots 400\text{ V}$                    | dv/dt                 | 100        | V/ns               |
| Reverse diode dv/dt, $V_{DS}=0\ldots 400\text{ V}$ , $I_{SD}\leq I_D$     | dv/dt                 | 50         | V/ns               |
| Operation and storage temperature                                         | $T_{stg}, T_j$        | -55 to 150 | $^{\circ}\text{C}$ |

**Thermal Characteristics**

| Parameter                                          | Symbol          | Value | Unit                 |
|----------------------------------------------------|-----------------|-------|----------------------|
| Thermal resistance, junction-case                  | $R_{\theta JC}$ | 0.5   | $^{\circ}\text{C/W}$ |
| Thermal resistance, junction-ambient <sup>4)</sup> | $R_{\theta JA}$ | 62    | $^{\circ}\text{C/W}$ |

**Electrical Characteristics** at  $T_j=25^{\circ}\text{C}$  unless otherwise specified

| Parameter                        | Symbol       | Min. | Typ. | Max. | Unit          | Test condition                                                       |
|----------------------------------|--------------|------|------|------|---------------|----------------------------------------------------------------------|
| Drain-source breakdown voltage   | $BV_{DSS}$   | 600  |      |      | V             | $V_{GS}=0\text{ V}$ , $I_D=1\text{ mA}$                              |
| Gate threshold voltage           | $V_{GS(th)}$ | 3.5  |      | 5.5  | V             | $V_{DS}=V_{GS}$ , $I_D=1\text{ mA}$                                  |
| Drain-source on-state resistance | $R_{DS(ON)}$ |      | 70   | 92   | m $\Omega$    | $V_{GS}=10\text{ V}$ , $I_D=20\text{ A}$                             |
|                                  |              |      | 180  |      |               | $V_{GS}=10\text{ V}$ , $I_D=20\text{ A}$ , $T_j=150^{\circ}\text{C}$ |
| Gate-source leakage current      | $I_{GSS}$    |      |      | 100  | nA            | $V_{GS}=20\text{ V}$ , $V_{DS}=0\text{ V}$                           |
|                                  |              |      |      | -100 |               | $V_{GS}=-20\text{ V}$ , $V_{DS}=0\text{ V}$                          |
| Drain-source leakage current     | $I_{DSS}$    |      |      | 10   | $\mu\text{A}$ | $V_{DS}=600\text{ V}$ , $V_{GS}=0\text{ V}$                          |
| Gate resistance                  | $R_G$        |      | 11   |      | $\Omega$      | $f=1\text{ MHz}$ , Open drain                                        |

### Dynamic Characteristics

| Parameter                                    | Symbol       | Min. | Typ. | Max. | Unit | Test condition                                                                              |
|----------------------------------------------|--------------|------|------|------|------|---------------------------------------------------------------------------------------------|
| Input capacitance                            | $C_{iss}$    |      | 2560 |      | pF   | $V_{GS}=0\text{ V}$ ,<br>$V_{DS}=50\text{ V}$ ,<br>$f=100\text{ kHz}$                       |
| Output capacitance                           | $C_{oss}$    |      | 157  |      | pF   |                                                                                             |
| Reverse transfer capacitance                 | $C_{rss}$    |      | 3.5  |      | pF   |                                                                                             |
| Effective output capacitance, energy related | $C_{o(er)}$  |      | 99.2 |      | pF   | $V_{GS}=0\text{ V}$ ,<br>$V_{DS}=0\text{ V}-400\text{ V}$                                   |
| Effective output capacitance, time related   | $C_{o(tr)}$  |      | 588  |      | pF   |                                                                                             |
| Turn-on delay time                           | $t_{d(on)}$  |      | 27   |      | ns   | $V_{GS}=10\text{ V}$ ,<br>$V_{DS}=400\text{ V}$ ,<br>$R_G=2\ \Omega$ ,<br>$I_D=20\text{ A}$ |
| Rise time                                    | $t_r$        |      | 46   |      | ns   |                                                                                             |
| Turn-off delay time                          | $t_{d(off)}$ |      | 87   |      | ns   |                                                                                             |
| Fall time                                    | $t_f$        |      | 4    |      | ns   |                                                                                             |

### Gate Charge Characteristics

| Parameter            | Symbol        | Min. | Typ. | Max. | Unit | Test condition                                                         |
|----------------------|---------------|------|------|------|------|------------------------------------------------------------------------|
| Total gate charge    | $Q_g$         |      | 58   |      | nC   | $V_{GS}=10\text{ V}$ ,<br>$V_{DS}=400\text{ V}$ ,<br>$I_D=20\text{ A}$ |
| Gate-source charge   | $Q_{gs}$      |      | 16   |      | nC   |                                                                        |
| Gate-drain charge    | $Q_{gd}$      |      | 26   |      | nC   |                                                                        |
| Gate plateau voltage | $V_{plateau}$ |      | 6.9  |      | V    |                                                                        |


### Body Diode Characteristics

| Parameter                     | Symbol    | Min. | Typ. | Max. | Unit | Test condition                                                                  |
|-------------------------------|-----------|------|------|------|------|---------------------------------------------------------------------------------|
| Diode forward voltage         | $V_{SD}$  |      |      | 1.3  | V    | $I_S=40\text{ A}$ ,<br>$V_{GS}=0\text{ V}$                                      |
| Reverse recovery time         | $t_{rr}$  |      | 139  |      | ns   | $V_R=400\text{ V}$ ,<br>$I_S=20\text{ A}$ ,<br>$di/dt=100\text{ A}/\mu\text{s}$ |
| Reverse recovery charge       | $Q_{rr}$  |      | 876  |      | nC   |                                                                                 |
| Peak reverse recovery current | $I_{rrm}$ |      | 11.7 |      | A    |                                                                                 |


### Note

- 1) Calculated continuous current based on maximum allowable junction temperature.
- 2) Repetitive rating; pulse width limited by max. junction temperature.
- 3)  $P_d$  is based on max. junction temperature, using junction-case thermal resistance.
- 4) The value of  $R_{\theta JA}$  is measured with the device mounted on 1 in square FR-4 board with 2oz. Copper, in a still air environment with  $T_a=25\text{ }^{\circ}\text{C}$ .
- 5)  $V_{DD}=100\text{ V}$ ,  $V_{GS}=10\text{ V}$ ,  $L=75\text{ mH}$ , starting  $T_j=25\text{ }^{\circ}\text{C}$ .


## Electrical Characteristics Diagrams




**Figure 1. Typ. output characteristics  $T_j=25^{\circ}\text{C}$**




**Figure 2. Typ. transfer characteristics**




**Figure 3. Typ. capacitances**




**Figure 4. Typ. gate charge**




**Figure 5. Drain-source breakdown voltage**




**Figure 6. Drain-source on-state resistance**




**Figure 7. Threshold voltage**




**Figure 8. Forward characteristic of body diode**




**Figure 9. Drain-source on-state resistance**




**Figure 10. Drain current**



**Figure 11. Typ. Coss stored energy**



**Figure 12. Safe operation area Tc=25°C**



## Test circuits and waveforms



**Figure 1. Gate charge test circuit & waveform**




**Figure 2. Switching time test circuit & waveforms**



**Figure 3. Unclamped inductive switching (UIS) test circuit & waveforms**



**Figure 4. Diode reverse recovery test circuit & waveforms**

**Package Information**


| Symbol | mm       |       |       |
|--------|----------|-------|-------|
|        | Min      | Nom   | Max   |
| A      | 4.40     | 4.50  | 4.60  |
| A1     | 0.00     | 0.10  | 0.25  |
| A2     | 2.20     | 2.40  | 2.60  |
| b      | 0.76     | -     | 0.89  |
| b2     | 1.23     | -     | 1.37  |
| c      | 0.47     | -     | 0.60  |
| c1     | 0.46     | 0.51  | 0.56  |
| c2     | 1.25     | 1.30  | 1.35  |
| D      | 9.10     | 9.20  | 9.30  |
| D1     | 8.00     | -     | -     |
| E      | 9.80     | 9.90  | 10.00 |
| E1     | 7.80     | -     | -     |
| e      | 2.54 BSC |       |       |
| H      | 14.90    | 15.30 | 15.70 |
| L      | 2.00     | 2.30  | 2.60  |
| L1     | 1.17     | 1.27  | 1.40  |
| L2     | -        | -     | 1.75  |
| L3     | 0.25 BSC |       |       |
| L4     | 4.60 REF |       |       |
| θ      | 0°       | -     | 8°    |
| θ1     | 1°       | 3°    | 5°    |

Version: TO263-J package outline dimension

### Ordering Information

| Package Type | Units/ Reel | Reels/ Inner Box | Units/ Inner Box | Inner Boxes/ Carton Box | Units/ Carton Box |
|--------------|-------------|------------------|------------------|-------------------------|-------------------|
| TO263-J      | 800         | 1                | 800              | 10                      | 8000              |

### Product Information

| Product          | Package | Pb Free | RoHS | Halogen Free |
|------------------|---------|---------|------|--------------|
| OSG60R092KT3ZF-F | TO263   | yes     | yes  | yes          |

### Legal Disclaimer

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics. With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Oriental Semiconductor hereby disclaims any and all warranties and liabilities of any kind, including without limitation, warranties of non-infringement of intellectual property rights of any third party.

For further information on technology, delivery terms and conditions and prices, please contact the Oriental Semiconductor sales representatives ([www.orientalsemi.com](http://www.orientalsemi.com)).

© Oriental Semiconductor Co.,Ltd. All Rights Reserved 