



General Description

OST200N120H7AF uses advanced Oriental-Semi's patented Trident-Gate Bipolar Transistor (TGBT™) technology to provide extremely low $V_{CE(sat)}$, low gate charge, and excellent switching performance. This device is suitable for mid to high range switching frequency converters.

Features

- Advanced TGBT™ technology
- Excellent conduction and switching loss
- Excellent stability and uniformity



Applications

- Induction converters
- Uninterruptible power supplies


Key Performance Parameters

Parameter	Value	Unit
$V_{CES, min} @ 25\text{ }^{\circ}\text{C}$	1200	V
Maximum junction temperature	175	$^{\circ}\text{C}$
$I_C, pulse$	800	A
$V_{CE(sat)}, typ @ V_{GE}=15\text{ V}$	1.40	V
Q_g	809	nC

Marking Information

Product Name	Package	Marking
OST200N120H7AF	TO247-plus-4L	OST200N120H7A

Package & Pin Information



Absolute Maximum Ratings at $T_{vj}=25\text{ }^{\circ}\text{C}$ unless otherwise noted

Parameter	Symbol	Value	Unit
Collector emitter voltage	V_{CES}	1200	V
Gate emitter voltage	V_{GES}	± 20	V
Transient gate emitter voltage, $T_P \leq 10\text{ }\mu\text{s}$, $D < 0.01$		± 30	V
Continuous collector current ¹⁾ , $T_C = 25\text{ }^{\circ}\text{C}$	I_C	400	A
Continuous collector current ¹⁾ , $T_C = 100\text{ }^{\circ}\text{C}$		200	A
Pulsed collector current ²⁾ , $T_C = 25\text{ }^{\circ}\text{C}$	$I_{C, \text{ pulse}}$	800	A
Power dissipation ³⁾ , $T_C = 25\text{ }^{\circ}\text{C}$	P_D	1250	W
Power dissipation ³⁾ , $T_C = 100\text{ }^{\circ}\text{C}$		625	W
Operation and storage temperature	T_{stg}, T_{vj}	-55 to 175	$^{\circ}\text{C}$

Thermal Characteristics

Parameter	Symbol	Value	Unit
IGBT thermal resistance, junction-case	$R_{\theta JC}$	0.12	$^{\circ}\text{C/W}$
Thermal resistance, junction-ambient	$R_{\theta JA}$	40	$^{\circ}\text{C/W}$

Electrical Characteristics at $T_{vj}=25\text{ }^{\circ}\text{C}$ unless otherwise specified

Parameter	Symbol	Min.	Typ.	Max.	Unit	Test condition
Collector-emitter breakdown voltage	$V_{(BR)CES}$	1200			V	$V_{GE}=0\text{ V}$, $I_C=0.5\text{ mA}$
Collector-emitter saturation voltage	$V_{CE(sat)}$		1.40	1.75	V	$V_{GE}=15\text{ V}$, $I_C=200\text{ A}$, $T_{vj}=25\text{ }^{\circ}\text{C}$
			1.63		V	$V_{GE}=15\text{ V}$, $I_C=200\text{ A}$, $T_{vj}=125\text{ }^{\circ}\text{C}$
			1.77		V	$V_{GE}=15\text{ V}$, $I_C=200\text{ A}$, $T_{vj}=175\text{ }^{\circ}\text{C}$
Gate-emitter threshold voltage	$V_{GE(th)}$	5.2	6.2	7.2	V	$V_{CE}=V_{GE}$, $I_C=0.5\text{ mA}$
Gate-emitter leakage current	I_{GES}			100	nA	$V_{CE}=0\text{ V}$, $V_{GE}=20\text{ V}$
Zero gate voltage collector current	I_{CES}			10	μA	$V_{CE}=1200\text{ V}$, $V_{GE}=0\text{ V}$

Dynamic Characteristics

Parameter	Symbol	Min.	Typ.	Max.	Unit	Test condition
Input capacitance	C_{ies}		43607		pF	$V_{GE}=0\text{ V}$, $V_{CE}=25\text{ V}$, $f=100\text{ kHz}$
Output capacitance	C_{oes}		495		pF	
Reverse transfer capacitance	C_{res}		31		pF	
Turn-on delay time	$t_{d(on)}$		197		ns	$V_{GE}=15\text{ V}$, $V_{CC}=600\text{ V}$, $R_G=5\ \Omega$, $I_C=200\text{ A}$
Rise time	t_r		54		ns	
Turn-off delay time	$t_{d(off)}$		312		ns	
Fall time	t_f		302		ns	
Turn-on energy	E_{on}		4.94		mJ	
Turn-off energy	E_{off}		17.27		mJ	
Turn-on delay time	$t_{d(on)}$		187		ns	$V_{GE}=15\text{ V}$, $V_{CC}=600\text{ V}$, $R_G=5\ \Omega$, $I_C=100\text{ A}$
Rise time	t_r		37		ns	
Turn-off delay time	$t_{d(off)}$		382		ns	
Fall time	t_f		339		ns	
Turn-on energy	E_{on}		2.01		mJ	
Turn-off energy	E_{off}		11.10		mJ	

Gate Charge Characteristics

Parameter	Symbol	Min.	Typ.	Max.	Unit	Test condition
Total gate charge	Q_g		809		nC	$V_{GE}=15\text{ V}$, $V_{CC}=960\text{ V}$, $I_C=100\text{ A}$
Gate-emitter charge	Q_{ge}		389		nC	
Gate-collector charge	Q_{gc}		143		nC	

Note

- 1) Calculated continuous current based on maximum allowable junction temperature.
- 2) Repetitive rating; pulse width limited by max. junction temperature.
- 3) P_d is based on max. junction temperature, using junction-case thermal resistance.

Electrical Characteristics Diagrams




Figure 1. Typical output characteristics
($T_{vj}=25\text{ }^{\circ}\text{C}$)




Figure 2. Typical output characteristics
($T_{vj}=150\text{ }^{\circ}\text{C}$)




Figure 3. Typical transfer characteristics
($V_{CE}=20\text{ V}$)




Figure 4. Typical capacitance
($V_{GE}=0\text{ V}$, $f=100\text{ kHz}$)




Figure 5. Typical gate charge







Figure 6. Gate-emitter threshold voltage



Package Information



SECTION C-C, D-D & E-E&F-F

Symbol	mm			Symbol	mm		
	Min	Nom	Max		Min	Nom	Max
A	4.90	5.00	5.10	D1	20.90	21.00	21.10
A1	2.31	2.41	2.51	D2	16.05	16.25	16.45
A2	1.90	2.00	2.10	D3	1.02	1.17	1.32
A3	0.80	0.90	1.00	D4	1.30	1.40	1.50
a	0.00	—	0.15	D5	1.60	1.70	1.80
a'	0.00	—	0.15	E	15.70	15.80	15.90
b	1.16	—	1.26	E1	13.06	13.26	13.46
b1	1.15	1.20	1.22	E2	1.10	1.20	1.30
b2	2.16	—	2.26	E3	2.58	2.68	2.78
b3	2.15	2.20	2.22	e	5.080 BSC		
b4	1.36	—	1.46	e1	2.540 BSC		
b5	1.35	1.40	1.42	L	19.80	19.92	21.00
b6	1.16	—	1.26	L1	3.90	4.10	4.30
b7	1.15	1.20	1.22	L2	2.55	2.70	2.85
b8	—	—	2.40	P	2.40	2.50	2.60
b9	—	—	1.60	R	1.90	2.00	2.10
b10	—	—	1.40	R'	1.90	2.00	2.10
c	0.59	0.625	0.66	T	9.75	9.95	10.15
c1	0.59	0.60	0.66	U	6.00	6.20	6.40
D	22.30	22.40	22.50	N	3.24	3.34	3.44

Version 1: TO247-plus-4L-J package outline dimension

Ordering Information

Package Type	Units/ Tube	Tubes/ Inner Box	Units/ Inner Box	Inner Boxes/ Carton Box	Units/ Carton Box
TO247-plus-4L-J	30	20	600	4	2400

Product Information

Product	Package	Pb Free	RoHS	Halogen Free
OST200N120H7AF	TO247-plus-4L	yes	yes	yes

Legal Disclaimer

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics. With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Oriental Semiconductor hereby disclaims any and all warranties and liabilities of any kind, including without limitation, warranties of non-infringement of intellectual property rights of any third party.

For further information on technology, delivery terms and conditions and prices, please contact the Oriental Semiconductor sales representatives (www.orientalsemi.com).

© Oriental Semiconductor Co.,Ltd. All Rights Reserved 