

General Description

This MOSFET uses advanced trench technology to provide excellent $R_{DS(ON)}$, low gate charge and operation with gate voltages as low as -2.5V. This device is suitable for use as a wide variety of applications.

Features

- High Dense Design
- Ultra Low On-Resistance
- Reliable and Rugged



Applications

- PWM applications
- Power mangement
- Load switch


Key Performance Parameters

Parameter	Value	Unit
V_{DS}	-30	V
$R_{DS(ON), max} @ V_{GS} = -10V$	80	m Ω

Marking Information

Product Name	Package	Marking
OSH3401	SOT-23	3401

Package & Pin information



Absolute Maximum Ratings at $T_j=25^{\circ}\text{C}$ unless otherwise noted

Parameter	Symbol	Value	Unit
Drain-source voltage	V_{DS}	-30	V
Gate-source voltage	V_{GS}	± 12	V
Continuous Drain Current	I_D	-3.0	A
Pulsed Drain Current ¹⁾	$I_{D,pulse}$	-15	A
Power Dissipation	P_D	1.0	W
Operation and storage temperature	T_{stg}, T_j	-55 to 150	$^{\circ}\text{C}$

Thermal Characteristics

Parameter	Symbol	Value	Unit
Thermal resistance, junction-ambient ²⁾	$R_{\theta JA}$	125	$^{\circ}\text{C/W}$

Electrical Characteristics at $T_j=25^{\circ}\text{C}$ unless otherwise specified

Parameter	Symbol	Min.	Typ.	Max.	Unit	Test condition
Drain-source breakdown voltage	BV_{DSS}	-30			V	$V_{GS}=0\text{ V}, I_D=-250\text{ }\mu\text{A}$
Gate threshold voltage	$V_{GS(th)}$	-0.6	-0.8	-1.3	V	$V_{DS}=V_{GS}, I_D=-250\text{ }\mu\text{A}$
Drain-source on-state resistance	$R_{DS(ON)}$		72	80	$\text{m}\Omega$	$V_{GS}=-10\text{ V}, I_D=-4\text{ A}$
Drain-source on-state resistance	$R_{DS(ON)}$		81	95	$\text{m}\Omega$	$V_{GS}=-4.5\text{ V}, I_D=-3.7\text{ A}$
Drain-source on-state resistance	$R_{DS(ON)}$		99	130	$\text{m}\Omega$	$V_{GS}=-2.5\text{ V}, I_D=-2\text{ A}$
Gate-source leakage current	I_{GSS}			± 100	nA	$V_{GS}=\pm 12\text{ V}, V_{DS}=0\text{ V}$
Drain-source leakage current	I_{DSS}			-1	μA	$V_{DS}=-30\text{ V}, V_{GS}=0\text{ V}$

Dynamic Characteristics

Parameter	Symbol	Min.	Typ.	Max.	Unit	Test condition
Input capacitance	C_{iss}		295		pF	$V_{GS}=0\text{ V}$, $V_{DS}=-15\text{ V}$, $f=1.0\text{ MHz}$
Output capacitance	C_{oss}		34		pF	
Reverse transfer capacitance	C_{rss}		24		pF	
Turn-on Delay Time	$t_{d(on)}$		8		nS	$V_{GS}=-4.5\text{ V}$, $V_{DS}=-15\text{ V}$, $R_L=5\ \Omega$, $R_{GEN}=2\ \Omega$
Turn-on Rise Time	t_r		8		nS	
Turn-Off Delay Time	$t_{d(off)}$		17		nS	
Turn-Off Fall Time	t_f		6		nS	

Gate Charge Characteristics

Parameter	Symbol	Min.	Typ.	Max.	Unit	Test condition
Total gate charge	Q_g		6.8		nC	$V_{GS}=-4.5\text{ V}$, $V_{DS}=-15\text{ V}$, $I_D=-3\text{ A}$
Gate-source charge	Q_{gs}		1.5		nC	
Gate-drain charge	Q_{gd}		1.4		nC	

Body Diode Characteristics

Parameter	Symbol	Min.	Typ.	Max.	Unit	Test condition
Source drain current (Body Diode)	I_{SD}			-3	A	$T_A=25^\circ\text{C}$
Diode forward voltage	V_{SD}			-1.2	V	$I_S=-3\text{ A}$, $V_{GS}=0\text{ V}$

Note: 1) Pulse width limited by maximum allowable junction temperature.
 2) Repetitive Rating: Pulse width limited by maximum junction temperature.

Electrical Characteristics Diagrams




Figure 1. Typ. output characteristics




Figure 2. Typ. transfer characteristics




Figure 3. Capacitance




Figure 4. Gate charge




Figure 5. Body-diode characteristics





Figure 6. $R_{DS(ON)}$ vs junction temperature

Package Information



Symbol	mm	
	Min	Max
A	0.900	1.150
A1	0.000	0.100
A2	0.900	1.050
b	0.300	0.500
c	0.080	0.150
D	0.280	3.000
E	1.200	1.400
E1	2.250	2.250
e	0.950 TYP	
e1	1.800	2.000
L	0.550 REF	
L1	0.300	0.500
θ	0°	8°

Version1 : SOT-23-V package outline dimension

Ordering Information

Package Type	Units/ Reel	Reels/ Inner Box	Units/ Inner Box	Inner Boxes/ Carton Box	Units/ Carton Box
SOT-23-V	3000	15	45000	4	180000

Legal Disclaimer

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics. With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Oriental Semiconductor hereby disclaims any and all warranties and liabilities of any kind, including without limitation, warranties of non-infringement of intellectual property rights of any third party.

For further information on technology, delivery terms and conditions and prices, please contact the Oriental Semiconductor sales representatives (www.orientalsemi.com).

© Oriental Semiconductor Co.,Ltd. All Rights Reserved 